

LEO auroral Charging Simulations with SPIS

Christian Imhof, Jörg Lange, Klaus Bubeck, Peter Hill, and Holger Mank
Astrium GmbH

All the space you need





Outline

- Modelling of the Satellite
- Simulation Settings
- Simulation Results
- Conclusions



Modelling of the Satellite

Trade off between detailed modelling and tolerable values for the computation time and memory demands.





Modelling of the Satellite

Trade off between detailed modelling and tolerable values for the computation time and memory demands.



≈ 9000 surface cells

≈ 215000 volume cells




Modelling of the Satellite

Material Distribution

Colour	Description	SPIS Material	Node #
Blue	Spacecraft Body; MLI	Kapton	0
Red	Radiators	ITO	0
Yellow	XBA, Thrusters	Steel	0
Purple	Solar Array Structure	Epoxy	5
Light Blue to Green	Solar Cell Coverglasses	CERS	1 - 4
Light Yellow to Green	Solar Cell Interconnects	Silver	0 - 4

SA Structure is connected to ground by a 10 k Ω bleeder resistor




Modelling of the Satellite

Material Distribution

Colour	Description	SPIS Material	Node #
Blue	Spacecraft Body; MLI	Kapton	0
Red	Radiators	ITO	0
Yellow	XBA, Thrusters	Steel	0
Purple	Solar Array Structure	Epoxy	5
Light Blue to Green	Solar Cell Coverglasses	CERS	1 - 4
Light Yellow to Green	Solar Cell Interconnects	Silver	0 - 4

SA Structure is connected to ground by a 10 kΩ bleeder resistor



Simulation Setup

Undisturbed LEO Conditions

- Charging behaviour in this plasma is well understood
- Consistency checks of the simulation model and parameters are possible

Plasma Parameters

Population	Density in cm^{-3}	Energy in eV
Electrons	10^5	0,2
Ions	10^5	0,1

Expected Results

- Floating potential of up to 80% of the solar generator maximum voltage (90 V) for negative grounding scheme
- Slightly negative floating potential for eclipse conditions
- No critical differential potentials on the structure to be expected

Simulation Setup

Auroral plasma environment

- Passing of the auroral zone is considered the worst case scenario


Auroral Plasma Properties

- Characterized by additional high energy electrons and a lowered density of the cold populations
- Parameters of the population are specified according to the SPENVIS population „Cold single Maxwellian and Fontheim electrons“

Chosen Maxwellian Parameters

Population	Density in cm ⁻³	Energy in eV
Electrons 1	809,9	0,2156
Electrons 2	1,482	12940
Ions 1	811,3	0,2156

Simulation Setup



Simulation Setup


Global Settings of the simulation

- Electrons modelled with Global Maxwell-Boltzmann Model
- Ions are modelled using the PIC model
- Non linear poisson solver
- all occuring secondary effects are considered
- Velocity of the satellite is addressed in order to simulate ram / wake effects
- secondary particle dynamics and external magnetic field are not considered
- maximum time step of 100 ms is chosen
 - due to the automatic time step algorithm the average time step was on the order of 30 – 60 ms
- satellite capacitance is set to 1 nF


Simulation Results

Undisturbed LEO conditions

eclipse; no voltage on the SA



sunlight; max. 90 V SA voltage




→ results are consistent with theory

Simulation Results


Undisturbed LEO conditions

surface potential

eclipse



sun




Simulation Results


Undisturbed LEO conditions

plasma potential

eclipse



sun




→ plasma potential is another proof of consistency

Simulation Results

Fontheim Plasma and sun

Floating Potential



Simulation Results


Fontheim plasma and sun

Potentials for $t = 80$ s

- All surfaces in the sun take on potentials close to 0 V
- Max. negative potential of -388 V in the aperture of the MSI
- Max. differential potential of 200 V
- No critical IPG on the solar array

Simulation time > 4 days

Memory costs \approx 7 GB



Simulation Results


Fontheim plasma and sun

Potentials for $t = 80$ s

- All surfaces in the sun take on potentials close to 0 V
- Max. negative potential of -388 V in the aperture of the MSI
- Max. differential potential of 200 V
- No critical IPG on the solar array

Simulation time > 4 days


Memory costs \approx 7 GB



Simulation Results

Fontheim Plasma and eclipse

Floating Potential




Simulation Results

Fontheim plasma and eclipse
Potentials for $t = 80$ s

- Max. negative potential of -622 V in the aperture of the MSI
- Solar array cover glasses still at a potential around **0 V** due to high secondary emission
➔ **IPG on the SA of -245 V**
- Max. differential potential of 380 V

Simulation time > 3 days

Memory costs ≈ 6 GB




Simulation Results

Fontheim plasma and eclipse
Potentials for $t = 80$ s

- Max. negative potential of -622 V in the aperture of the MSI
- Solar array cover glasses still at a potential around **0 V** due to high secondary emission
➔ **IPG on the SA of -245 V**
- Max. differential potential of 380 V

Simulation time > 3 days

Memory costs \approx 6 GB



Simulation Results

Influence of material distribution


Under investigation:

- ITO coated radiators vs. blank Teflon radiators
- performed on model with shorter SA for simulation time reasons


Simulation Results

Fontheim Plasma and shade

ITO coated radiators



Teflon radiators




Simulation Results

Fontheim plasma and eclipse

Potentials for $t = 80$ s

- max. potentials on the satellite with uncoated radiators are nearly doubled compared to the version with coated radiators
- IPG on the solar array rises to 700 V
 - ➔ high threat of ESD / arcing



Conclusions

Simulation Results

- Simulations reveal potentially dangerous potentials on the satellite
- Calculated potentials can be used as input for ESD analysis

SPIS Tool

- Possibility to assess the risks to the satellite due to surface charging
- Chance to gain a better understanding of the charging phenomena
- Impact of different materials on the charging process can be assessed
- Software has to be handled with extreme care to avoid crashes and inconsistent results
- Further improvement on the numerical algorithms and on the usability are desirable